


M.O.L.E.™ EV6

Thermal Profiler

An Evolution in Thermal Profiling

With a revolutionary new design, M.O.L.E.™ EV6 brings deep data collection and touch screen convenience to thermal profiling. The traveling thermal profiler allows configuration, measurement and data analysis right on the device – providing immediate actionable information, saving time and reducing the requirement for intensive operator training. Using a familiar smartphone-like capacitive touch screen, users now have shop floor data literally at their fingertips. The six-channel M.O.L.E. EV6 integrates with all ECD RIDER™ machine quality management technologies for a truly scalable approach, made easier with visual, touch screen control.



Profile Screen



KPI Table Screen



Integrates with all ECD RIDERs for scalable machine quality management

FEATURES | BENEFITS

- ✓ **Built in LED touch screen display.**
 - Simple and immediate status confirmation.
 - Color coded, pass/fail, numerical key performance data.
 - Live temperature readings.
 - Saves time, reduces training requirements.
- ✓ **Flexibility**
 - 6 thermocouple inputs.
 - Multiple thermocouple types supported.
 - Wireless, real-time operation via Bluetooth® (optional).
- ✓ **User-Friendly on-screen information**
 - Built-in calibration reminders
 - Battery life/charge indicators
 - Memory status indicator
- ✓ **Built to last**
 - High capacity, off the shelf Li-Po rechargeable battery.
 - Automatic shutdown if internal temperature is too high.
 - ESD protected inputs.
 - USB-C communication and charging.



60 Years of Excellence, and Still Growing Strong

www.ecd.com



WHAT'S IN THE KIT



STANDARD THERMAL PROFILER KIT ECD P/N: E61-3806-00

- M.O.L.E.™ EV6 thermal profiler
- 260L stainless steel thermal barrier
- 260L Yellow Jacket thermal barrier cover
- One set of 6 glass color-indexed 36-gauge thermocouples
- M.O.L.E.™ MAP software
- PC USB-C cable (set-up & download)
- Universal power pack charger
- Quick reference guide
- Carrying case
- Calibration certificate from ECD's ISO 17025-accredited lab

SPECIFICATIONS:

DISPLAY

IPS TFT display
240 x 363 dot matrix
High brightness LED backlight
Any angle viewing direction

THERMOCOUPLE INPUTS (UP TO 12)

ECD micro-thermocouples: Type K, T, J, E, N, R, S & B
%RH: ECD VaporWATCH® RH sensor

DATA ACQUISITION

Sampling interval: 100 samples/second to 10 minutes/sample
Data points: 16 million or 200 data runs (whichever comes first)
Accuracy: +/- 0.5°C (0.9°F)
Resolution: 0.0056°C (0.01°F)*
Noise rejection: 50-60 Hz*
Measurement range: -200°C to 1,200°C (-328°F to 2,192°F)

POWER

Battery: LiPo (lithium polymer ion) - rechargeable, 1100mAh
Charge protection: Optimized for lithium polymer
Charge time: Full - < 4 hours
Charge run time: Full - 6 to 8 Hours
Battery life: 300 charging cycles or 3 years (minimum)
Charger input current: 60 ma via USB interface

.....
* >= 0.05 seconds/sample

COMMUNICATIONS

Interface: USB 2.0 compliant (charge; upload; download)
Cable: USB type A to USB-C, 1m (3')

PHYSICAL

Dimensions (L x W x H):

- Profiler: 152.4mm (6.0") x 89mm (3.5") x 9.41mm (0.37")
- Barrier: 254.0mm (10.0") x 104mm (4.1") x 26.9mm (1.06")
- Yellow Jacket: 264.2mm (10.4") x 115mm (4.53") x 32.5 (1.28")

Weight:

- Profiler: 0.204 kg (7.2 oz)
- Barrier: 0.75 kg (26.4 oz)
- Yellow Jacket: 0.07 kg (2.4 oz)

Operational range (profiler): -40°C to +85°C (-40°F to 185°F)

Humidity: 0-85% RH (non condensing)

COMPLIANCE



PATENT

Patent No. 7,653,502

WARRANTY

2 years parts and labor

PRODUCT PAGE

ecdusa.co/mev6

All information is subject to change at any time without notice.



ECD WORLD HEADQUARTERS
(North America - US, Canada)
4287-B SE International Way
Milwaukie, Oregon 97222 U.S.A.
Tel: +1 800 323 4548
E-Mail: sales@ecd.com
Web: www.ecd.com

APAC
(Asia-Pacific, China, India)
Singapore Office
Mobile: +65 9692 6822
E-Mail: ecd.asia@ecd.com

EMEA
(Europe, Middle East, Africa)
UK Office
Mobile: +44 (0) 7903 252560
E-Mail: ecd.europe@ecd.com

LATAM
(Mexico, Central, South America)
Houston, TX U.S.A. Office
Phone: +1 503 659 6100 x 250
Mobile: +1 832 533 0046
E-Mail: ecd.latam@ecd.com